

Product Information

PROFIX CF-4/CE/CF 10W-30 15W-40 (mineral oil)

The PROFIX CF-4/CE/CF series is oil for high-performance diesel engines which show power to a high output diesel engine equipped with turbo superchargers.

This product has superior cleanliness-related abrasion characteristics-resistant by combining the most suitable additive with base oil.

Approvals

API CF-4 級

Characteristics (Typical Figures)

SAE Grade		10W-30	15W-40
Viscosity at 100°C	mm ² /s	9.736	13.2
Viscosity at 40°C	mm ² /s	63.28	97.7
Viscosity at	mPa.s	6,200(-25°C)	6,600(-20°C)
Viscosity Index	-	137	133
Flash Point COC	°C	238	230
Density at 15°C	g/cm ³	0.8811	0.886

PROPERTIES AND PERFORMANCE OF PROFIX CF-4/CE/CF

- This product is available for the diesel car including an old vehicle.
- This product does not fit use on designation or a recommended vehicle with JASO DH -1, JASO DH -2, JASO DL-1 standardized goods.
- This product keeps an engine high in the clean nature in a clean state, and even an intense heat place prevents overheat because I am superior in high temperature stability.
- Oil slick retentivity is strengthened by the effective combination of mineral oil and the additive, and this product protects an engine and draws higher engine performance.