

Product Information

PROFIX DH-2 10W-30 15W-40

The PROFIX DH-2 series is oil for DPF (Diesel Particulate Filter) which cleared JASO DH-2 standard of JASO(Japan Automotive Standards Organization) and diesel engines which are most suitable for a diesel car of the catalyst device wearing.

This oil is low soot oil to boast of the high durability to having superior cleanliness-related abrasion characteristics-resistant by combining the additive which is most suitable for base oil. (mineral oil)

Approvals

JASO DH-2

Characteristics (Typical Figures)

SAE Grade		10W-30	15W-40
Viscosity at 100°C	mm ² /s	11.4	14.8
Viscosity at 40°C	mm ² /s	74.9	111
Viscosity at	mPa.s	6,500(-25°C)	6,600(-20°C)
Viscosity Index	-	144	138
Flash Point COC	°C	224	232
Density at 15°C	g/cm ³	0.877	0.883

PROPERTIES AND PERFORMANCE OF PROFIX DH-2 PRODUCTS

- This oil is available for all diesel cars from the vehicle which is old with the oil for exclusive use of a diesel car equipped with DPF (Diesel Particulate Filter) corresponding to the diesel regulation to the latest vehicle of the DPF wearing.
- ※This oil does not fit use on designation or a recommended vehicle with JASO DL-1.
- This oil has high oil slick retentivity by the effective combination of mineral oil and the additive and shows engine protection performance under the severe terms of use and draws engine performance.
- This oil keeps high cleanliness characteristics from low temperature to a high temperature in all domains and keeps an engine clean under various operating conditions.
- "Certification mark" of JASO sticks to a package. As for this mark, it is forgiven use indication only the oil which caught the certification of JASO.