

Product Information

PROFIX DL-1 5W-30

PROFIX DL-1 5W -30 is oil for DPF (Diesel Particulate Filter) which cleared latest standard JASO DL-1 of JASO(Japan Automotive Standards Organization) and diesel engines which are most suitable for a diesel car of the catalyst device wearing.

This oil passes a severe standard by combining the most suitable additive with base oil using high viscosity index group oil (Hi-VI composition oil) and has superior cleanliness-related abrasion characteristics-resistant and improves mileage performance-saving drastically. (Semi synthetic oil)

Approvals

JASO DL-1

Characteristics (Typical Figures)

SAE Grade		5W-30
Viscosity at 100°C	mm ² /s	10.5
Viscosity at 40°C	mm ² /s	63.4
Viscosity at	mPa.s	4,300(-25°C)
Viscosity Index	-	151
Flash Point COC	°C	238
Density at 15°C	g/cm ³	0.856

PROPERTIES AND PERFORMANCE OF PROFIX DL-1 5W-30

- This oil is oil for exclusive use of the diesel car which carried DPF (Diesel Particulate Filter) for cars corresponding to the diesel regulation.
- ※This oil does not fit use on designation or a recommended vehicle with JASO DH -1 and JASO DH-2.
- Oil slick retentivity is strengthened by effective combination of high viscosity index group oil (Hi-VI composition oil), and this oil shows engine protection performance under the severe terms of use. And this oil protects an engine in a high temperature, the high load and draws higher engine performance.
- This oil improves high temperature oxidation stability by effective combination of high viscosity index group oil (Hi-VI composition oil) and prevents deterioration of oil exposed to the high temperature in the engine and maintains high lubrication performance for a long term.
- This oil keeps high cleanliness characteristics from low temperature to a high temperature in all domains and keeps an engine clean under various operating conditions.

- This oil be superior to start characteristics in the cold districts, and the particularly low temperature flow performance prevents the partial abrasion at the time of the start. In addition, I draw engine performance by superior lubrication performance effectively.
- "Certification mark" of JASO sticks to a package. As for this mark, it is forgiven use indication only the oil which caught the certification of JASO.